

## MM3E Micromanipulator with encoded axes

Based on the hugely successful MM3A-EM micro-manipulator, the MM3E exhibits the same compactness, precision, and stability combined with closed-loop positional feedback. This enhancement provides the means to improve the system's ease of use (e.g. by defining parking and working positions that can be addressed at the click of a button).



ACTUAL SIZE

The MM3E is fully compatible with virtually any SEM or FIB/SEM on the market. It comes with an intuitive, drag&drop-style control software which provides an easy means for positioning the tool tip in three dimensions inside your SEM or FIB/SEM tool.

The software performs coordinate transformations so that the MM3E behaves as a cartesian system with a reproducibility of a few micrometers. With the optional encoded axial rotation drive, the specimen can be rotated concentrically in the vicinity of the sample.

**Give your microscope a hand:** use the MM3E to add new capabilities and functionality to your instrument.

### APPLICATIONS

In-situ lift-out

Electrical probing (FA)

Nanomanipulation

### PLUG-IN TOOLS

Rotational tip

Microgripper

Low current measurement kit

Micro soldering unit

Microinjector

Gas Injection System

Force measurement system



# MM3E Micromanipulator with encoded axes

## More compact and more flexible

- Small footprint with non-cartesian axes used in a cartesian manner
- Plug-and-play system with modular components and a range of plug-in tools
- Interfacing solutions for most SEM/FIB tools
- Fast setup
- Effortless work with multiple manipulators

## Clearer and simpler

- Result-oriented operation which leads to increased throughput
- Intuitive software control interface
- User-friendly and easy to learn
- Quick and easy probe tip exchange without the need to vent the chamber

## More robust and more stable

- Compact construction delivers higher resonance frequencies
- Excellent stability
- Reliable operation (one year endurance test)
- Virtually unsusceptible to vibrations
- Fast pre-positioning by hand

## Faster and more precise

- Extensive working range (100 cm<sup>3</sup>)
- Coarse and fine displacement in one drive

## Technical specifications

- Resolution XY < 0.5 nm
- Resolution Z < 0.02 nm
- Resolution axial-R < 0.5e-6°
- Repeatability XYZ < 2 μm
- Repeatability axial-R < 0.02°
- Drift < 1 nm/min
- Compucentric rotation concentricity ~30 μm

## Software features

- Drag&drop control in both SEM (XY) and FIB (XZ) views
- Define and store absolute positions
- Run user-generated macros
- Communication with SEM allows automatic speed adjustments, correct operation at various scan rotations, etc.
- Precise, cartesian X,Y, and Z motion wrt the SEM's chamber
- Easy access to park, standby, and restore positions
- Can also be used to drive the (optional) coaxial rotation motor as well as the (optional) microgripper
- Compucentric rotation!

Contact us at  
[info@kleindiek.com](mailto:info@kleindiek.com)  
 or find your local agent at  
[www.kleindiek.com](http://www.kleindiek.com)

Compucentric rotation within a field of view of 30 μm

1 mm